


► Feed direction  
 $w = 13 \text{ mm}$ ,  $l = 65 \text{ mm}$   
 $c_1 = 12 \text{ mm}$ ,  $c_2 = 65 \text{ mm}$   
 $p_1 = 25 \text{ mm}$ ,  $p_2 = 130 \text{ mm}$   
 Open area: 14.27%



Material (desired formats also available in powder-coated finish)	Material thickness in mm	Desired format	Small format 1000 x 2000 mm	Medium format 1250 x 2500 mm	Large format 1500 x 3000 mm	Weight kg/m <sup>2</sup>
<b>Steel</b>						
	1.50	501763	153263	153438	153622	10.1
	2.00	502521	153264	153439	153623	13.5
<b>Pre-galvanised</b>						
DX51D	1.50	501661	157110	157111	157112	10.1
	2.00	502433	157113	157114	157115	13.5
<b>Aluminium</b>						
EN AW-1050A H24	1.50	501004	150160	150351	150538	3.5
	2.00	501860	150161	150352	150539	4.6
// PVC coated on one side	1.50	501088	150649	150769		3.5
	2.00	501943	150650	150770		4.6
EN AW-5005 H24 EQ, PVC 1 side	1.50	501166	150958			3.5
// pre-anodised 2 sides E6/CO, PVC 1 side	2.00	502073	151368	151427	151486	4.6
<b>Stainless steel</b>						
X5CrNi18-10 2B AISI 304	1.50	501399	152254	152398	152525	10.1
// polished 1 side grain 240, PVC 1 side	1.50	501501	152688	152785	152874	10.1
// polished 2 sides grain 240, PVC 2 sides	1.50	503225	157652	158147	158148	10.1
X2CrNiMo17-12-2 2B AISI 316 L	1.50	501308	151984		152102	10.1

